



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS PER QQ-B-626
- 2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 3. BERYLLIUM COPPER PER QQ-C-530
- 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 5. TEFLON MIL-P-19468

10	SHELL	NOTE 1	NOTE 2	1	N5000-1-B
9	GASKET	SILICONE	RED	1	GS-156/8X15
8	RETAINER RING	SUS 304	NATURAL	1	N5000-7-C
7	GASKET	SILICONE	RED	1	GS-6/43X06
6	RETAINER RING	NOTE 3	NATURAL	1	SMA5000-4-B
5	CONTACT BODY	NOTE 1	NOTE 2	1	N5000-5
4	CONTACT PIN	NOTE 1	NOTE 4	1	RSA-3453-4
3	INSULATOR	NOTE 5	NATURAL	1	RSA-3453-3
2	BODY	NOTE 1	NOTE 2	1	RSA-3453-2
1	SHELL	NOTE 1	NOTE 2	1	SMA5000-1-C
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS			PART NO.	NM-SMAM-NT3G-50	
UNLESS OTHERWISE SPECIFIED TOLERANCES			APPROVED	DATE	10-11-01'
0.5-6	= ±0.2		CHECKED	DATE	10-11-01'
6-30	= ±0.4		DRAWN	DATE	10-11-01'
30-120	= ±0.6				
120-315	= ±1				
315-1000	= ±1.6				
1000-2000	= ±2.4				
SCALE	3/1	ISSUE	A	FILE NO.	

<h1>Amphenol</h1>	
TITLE N MALE TO SMA MALE ADAPTOR	
DRAWING NO. KJ-NM-SMAM-NT3G-50	
ITEM NO.	