

**COAXIAL CONNECTOR, BNC, 50 Ohm, Right angle cable plug (male)**

16\_BNC-50-2-3/133\_N

**Properties**

- Useful for frequently coupled and uncoupled connections
- Available for 50 ohm and 75 ohm applications
- Applicable in frequencies up to 4 GHz



Product configuration		
Interface type	Gender	Standard
BNC	plug	IEC 60169-8_MIL-STD-348A/301_CECC 22120
Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating
Electrical data		
Impedance	50 $\Omega$	
Interface frequency	4 GHz	
Mechanical data		
Weight	0.0162 kg	
Mating cycles	500	
Cable entry centre contact	soldered	
Cable entry outer contact	crimped	
Environmental data		
Operation temperature	-65 °C ... 165°C	

**COAXIAL CONNECTOR, BNC, 50 Ohm, Right angle cable plug (male)**

16\_BNC-50-2-3/133\_N

<b>Ordering Information Table</b>		
Item number	Item description	Packaging type
22540168	16_BNC-50-2-3/133_NE	Single
22648628	16_BNC-50-2-3/133_NH	Bulk 100 pcs

  

<b>Suitable cables</b>	
Cable group	U2 - 2 mm / 50 Ohm
Suitable cables	RG_316_/U
	RG_188_A/U
Additional cables	RG_174_/U

  

<b>Additional Information</b>	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P3164 / Date of publication: 25.11.2023 / uncontrolled copy